

Crystic VE 671-03

Vinyl Ester Resin

Introduction

Crystic VE671-03 is a bisphenol A epoxy based, vinyl ester resin designed for vacuum infusion.

Applications

Crystic VE671-03 was designed for use in closed mould applications such as vacuum infusion and centrifugal casting processes. It is recommended for the manufacture of fibre reinforced composite tanks, vessels, ducts etc. for use in chemical processing applications.

Features and Benefits

Crystic VE671-03 has excellent resistance to a wide range of chemical substances (acid, alkalies and oxidising agents).

Approvals

Crystic VE671-03 is approved by Lloyd's Register of Shipping for use in the construction of craft under their survey.

Product Characteristics

FORMULATION

Crystic VE 671-03 should be allowed to attain workshop temperature (18°C-25°C) before use. It requires the addition of a catalyst and accelerators to start the curing reaction.

The correct amount of Accelerator **G** (1% Cobalt) and Acetyl Acetone should be stirred into the resin. The recommended catalyst for this system is Trigonox 239, which should be added at 2% into the resin and thoroughly dispersed. The geltime can be adjusted by varying the levels of Acetyl Acetone
N.B. Catalyst and accelerator must not be mixed directly together, as they can react with explosive violence.

TYPICAL PROPERTIES

The following tables give typical properties of Crystic VE 671-03 when tested in accordance with the appropriate BS, or BS EN ISO test method.

Property		<u>Liquid Resin</u>
Acid value	mgKOH/g	max. 8.5
Viscosity Brookfield RVT @ 25°C	mPas	150 - 200
Volatile content	%	53 ± 2
Shelf life (max 25 °C, in the dark)	months	6
Geltime @ 25°C using: 2% Acc.G & 2% Trigonox 239	minutes	20 - 30
Geltime @ 25°C using: 2% Acc.G, 0.06 % Acetyl acetone & 2% Trigonox 239	minutes	110

Mechanical Properties

Property		<u>Cured cast resin</u>
Tensile strength**	MPa	80
Tensile modulus**	GPa	3.4
Elongation to break**	%	4 – 5
Flexural strength**	MPa	125
Barcol hardness**		45
HDT ***	°C	95 - 100
Water absorption**: 7 days	mg	35

** Curing Schedule: 24 hrs at 20°C followed by 3 hrs at 80°C.

***Curing Schedule: 24 hrs at 20°C followed by 5 hrs at 80°C and then 3 hrs at 120°C.

Laminate Property		at different temperature					
		23°C	65°C	93°C	107°C	121°C	149°C
Temperature	(°C)	23°C	65°C	93°C	107°C	121°C	149°C
Flexural Strength	(MPa)	208	198	189	101	34	22
Flexural Modulus	(GPa)	7.6	6.9	5.9	3.4	3.3	1.6
TensileStrength	(MPa)	152	172	145	124	76	50
TensileModulus	(GPa)	9.9	10.2	8.5	6.3	4.3	-
CompressiveStrength	(MPa)	1185	-	-	-	-	-
Glass Content	(%)	40					
Laminate Construction:		V/M/M/WR/M/WR/M					

V = veil, M = CSM, W = woven roving



Scott Bader Middle East Limited
P.O. Box 16785 Jebel Ali Free Zone, Dubai, U.A.E.
Telephone: +971-4-8835025, Facsimile: +971-4-8835319
Email: info@scottbader.co.ae, Website: www.scottbader.com



POST CURING

Satisfactory laminates for many applications can be made from Crystic VE671-03 by curing at workshop temperature (25°C). However, for optimum properties and long term performance laminates must be post cured before being put into service. Mouldings should be allowed to cure for 24 hours at 25°C and then be oven cured for a minimum of 3 hours at 80°C. Post curing at 100°C is advisable if mouldings are to operate at high temperatures.

Storage

Crystic VE 671-03 should be stored in the dark in suitable closed containers. It is recommended that the storage temperature should be less than 20°C where practical, but should not exceed 30°C.

Packaging

Crystic VE 671-03 is supplied in 200kg drums.

Health & Safety

Please see separate Material Safety Data Sheet.

October 2008



Scott Bader Middle East Limited
P.O. Box 16785 Jebel Ali Free Zone, Dubai, U.A.E.
Telephone: +971-4-8835025, Facsimile: +971-4-8835319
Email: info@scottbader.co.ae, Website: www.scottbader.com





Scott Bader Middle East Limited

P.O. Box 16785 Jebel Ali Free Zone, Dubai, U.A.E.

Telephone: +971-4-8835025, Facsimile: +971-4-8835319

Email: info@scottbader.co.ae, Website: www.scottbader.com

